



Carbon, Flexback, Hardedge

Carbon steel is inexpensive & readily available with a variety of tooth configurations & widths.

Features:

Heat treated European steel, High Alloy, Carbon steel. Tooth hardness 64-67 Rc. Back hardness 28-35 Rc.

Advantages:

Fast, clean cuts. Fatigue resistant at high speeds. Multiple widths for contour and straight cuts.

Benefits:

High productivity in wood cutting.

Low cost.

Excellent wear resistance in wood applications.


Applications:

For hard and soft wood cutting and re-sawing. For plastic, cork, fiberglass, graphite, aluminum, brass, bronze, cast iron, lead, zinc, etc.

To Order:

We will weld your band saw blade to ANY length. Specify length x Width x TPI (teeth per inch)

Category: BSB



1.14=7/8" pitch 1.3=3/4" pitch 3s,4s,6s - Skip tooth

TPI Hook		4 skip	4s,4,6s,6	3s,3,4s,4,6	3s,3,4s,4,6	2,3,4,6	2,3,4,6	1.14,1.3	1.14,1.3	1.14	1.3
TPI Raker	14,18	10,14,18	8,10,14,18	8,10,14,18	8,10,14,18	8,10,14,18	8,10,14				
Thickness	(.025")	(.025")	(.025")	(.025")	(.025")	(.032")	(.035")	(.035")	(.042")	(.045")	(.035")
Width	1/8"	3/16"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/4"	1 1/2"	2"