



Adjustable Countersink



Carbide Tipped,
2 Flutes




One Countersink fits all drill diameters from 1/8" (3.0mm) to 9/32" (7.2mm).
 Perfect grip of the two Cutting Teeth over the drill by means of screws, allowing easy setting of drilling and countersink depth in ONE PASS.
 Two Carbide Tipped Cutting Teeth for clean cuts and longer tool life.
 Each Countersink supplied with its Key in an attractive blister pack with sliding card.
 Recommended drills for ultimate performance use DIMAR's Machine Drills 205-D, Metric or Inch sizes.

Drill bit not included.

Tool no.	Countersink Dia.	Drill Dia.	B	Length	Category
202-CS	13/32" (10.0mm)	1/8" (3.0mm)	12mm	32mm	J
	27/64" (10.7mm)	9/64" (3.5mm)			
	29/64" (11.5mm)	5/32" (4.0mm)			
	15/32" (12.0mm)	3/16" (4.5mm)			
	1/2" (12.5mm)	13/64" (5.0mm)			
	33/64" (13.0mm)	7/32" (5.5mm)			
	17/32" (13.5mm)	15/64" (6.0mm)			
	9/16" (14.0mm)	1/4" (6.5mm)			
	37/64" (14.7mm)	9/32" (7.2mm)			

Replacement parts: Screw 1930463; Key 1940030



A simple to use table on the back of the package, will guide you through selecting the right drill for the job.
 Tip:
 Install the 202-CS upside down on your drill, and you got yourself an Adjustable Drill Stopper for precise drilling depth, at no extra cost.

